

# HPD II (High Pressure Diffuser)

Aerosol Monitoring Accessory

*Reduces the pressure of gases for particle counters operating at atmospheric pressure*



*Without measurement there is no control*

The HPD II reduces the pressure of high purity, high pressure gas to near atmospheric pressures to allow for accurate sampling of aerosol particle size channels of  $\geq 0.1 \mu\text{m}$  by PMS particle counters with a volumetric sample flow rate of 1.0 CFM. The HPD works by diffusing some of the gas out of the system, allowing the particle counter's flow-metering system to function as designed. The PMS particle counters that the HPD II is compatible with includes AirNet, IsoAir, Lasair Pro, and Lasair III.

The HPD II will effectively reduce the pressure of a gas line from 150 psi to atmospheric pressure and is compatible with non-toxic, non-flammable gases such as Clean Dry Air (CDA), nitrogen ( $\text{N}_2$ ), argon (Ar), and carbon dioxide ( $\text{CO}_2$ ). See the table below for a visualization of what particle counters are compatible with which gases.

HPD II is available in two configurations:

- HPD II-100 for gas lines between 40 and 100 psi
- HPD II-150 for gas lines between 100 and 150psi

See the full table on the next page of gas pressure capabilities.

Particle Counter	CDA	$\text{N}_2$	Ar	$\text{CO}_2$	$\text{O}_2/\text{He}/\text{Ne}$
Airnet	Y	Y	N	N	N
Lasair III 110	Y	Y	N	N	N
Lasair III 310	Y	Y	Y	N	N
IsoAir 310P	Y	Y	Y	N	N
IsoAir Pro-E/Plus	Y	Y	Y	Y	N
Lasair Pro	Y	Y	Y	Y	N
HPGP 101-C	Y	Y	Y	Y	Y

## BENEFITS

- Two models to reduce high-pressure gas between 40 – 100 psi or 75 - 150 psi to about atmospheric pressure
- Use in conjunction with a Lasair II-110 or Lasair III-110 particle counter to measure particles as small as  $0.1 \mu\text{m}$  in CDA, nitrogen, carbon dioxide, or argon
- Can be used with Clean Dry Air (CDA), argon (Ar), nitrogen ( $\text{N}_2$ ), carbon dioxide ( $\text{CO}_2$ ), or other non-toxic inert gases (see table for compatible gases)
- No external flow meters needed
- Economical monitoring of pressurized gases with atmospheric pressure particle counters

## FEATURES

- Specifically designed for use with the 1.0 CFM aerosol particle counters
- No moving parts to wear
- Exhaust filter prevents possible room contamination
- Particle counter can remain on, even when gas supply is off
- Stainless steel construction

## APPLICATIONS

- AirNet: 310, 510
- IsoAir: 310P, Pro-E, Pro-Plus
- Lasair Pro 310
- Lasair III: 110, 310, 310P

# HPD II (High Pressure Diffuser)

Aerosol Monitoring Accessory

Specifications

Pressure	See additional table below
Applicable Sample Flow Rate	1.0 CFM
Particle size range	0.1 – 1.0 µm
Environment	Temperature: 50 – 90 °F (10 – 32 °C). Humidity: Non-condensing.
Material	Enclosure: 316L stainless steel body, exhaust filter Gaskets: 316 stainless steel, Buna-N O-rings
Inlet fitting	Male 4-VCR fitting, #4 size, class 316L stainless steel with Ruby orifice
Exhaust fitting	3/8" ID with O-ring seal
Tubing length	1 m (39.4 in) maximum
Dimensions (h, w, d)	5.1 x 9.8 x 5.5 in (13 x 25 x 14 cm)
Weight	5.8 lb (2.6 kg)
Compatible instruments	See the Applications section on the previous page

	Flow Rate	CDA	Nitrogen	Argon	CO2
<b>HPD II 100</b>	<b>1.0 CFM</b>	40-100 psi	40-100 psi	40-100 psi	40-100 psi
<b>HPD II 150</b>	<b>1.0 CFM</b>	75 - 150 psi	75 - 150 psi	75 - 150 psi	75 - 150 psi

**System components included:** mounting brackets and exhaust tubing to particle counter

**Not included:** particle counter, ISPs sample tubing, communications cables, PC, FacilityNet or Pharmaceutical Net software

## HEADQUARTERS

5475 Airport Blvd  
Boulder, Colorado 80301 USA  
T: +1 303 443 7100

Instrument Service & Support  
T: +1 800 557 6363

Customer Response Center  
T: +1 877 475 3317  
E: info@pmeasuring.com

[www.pmeasuring.com](http://www.pmeasuring.com)  
[info@pmeasuring.com](mailto:info@pmeasuring.com)



## GLOBAL OFFICES

AUSTRIA  
T: +43 512 390 500  
E: pmsaustria@pmeasuring.com

BENELUX  
T: +32 10 23 71 56  
E: pmsbelgium@pmeasuring.com

BRAZIL  
T: +55 11 5188 8227  
E: pmsbrazil@pmeasuring.com

CHINA  
T: +86 21 6113 3600  
E: pmschina@pmeasuring.com

FRANCE  
T: 33(0)1 60 10 32 96  
E: pmsfrance@pmeasuring.com

GERMANY  
T: +49 6151 6671 632  
E: pmsgermany@pmeasuring.com

ITALY  
T: +39 06 9053 0130  
E: pmsrl@pmeasuring.com

JAPAN  
T: +81 44 589 3498  
E: pmsjapan@pmeasuring.com

KOREA  
T: +82 55 2271 5106  
E: pmskorea@pmeasuring.com

MEXICO  
T: +52 55 2271 5106  
E: pmsmexico@pmeasuring.com

NORDIC  
T: +45 707 028 55  
E: pmsnordic@pmeasuring.com

PUERTO RICO  
T: +1 787 718 9096  
E: pmspuertorico@pmeasuring.com

SINGAPORE  
T: +65 6496 0330  
E: pmsingapore@pmeasuring.com

SWITZERLAND  
T: +41 71 987 01 01  
E: pmsswitzerland@pmeasuring.com

TAIWAN  
T: 886-3-5525300 Ext: 301  
E: pmstaiwan@pmeasuring.com



Airnet®, Lasair®, and IsoAir® are registered trademarks of Particle Measuring Systems, Inc. All other trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. ©2022 Particle Measuring Systems, Inc. All rights reserved. 04222022